


CTP WARNINGLIGHTS









Spherical LED Head:

Description	Part No.	Features
	CDLS306-AW	Kit includes a snap-on polycarbonate black bezel that will hide the screw heads for a clean installation
		· 25 customer selectable flash patterns, including steady on
		Maximum light output in a minimum package
		No need to install a separate flasher unit; it's built into this miniature housing
		Lens has diffusing optics for wider coverage
		Circuitry is fully encapsulated within the housing for vibration and water resistance
		Interior/exterior mount
SPHERICAL LED HEAD - AMBER/WHITE		· 10-30V DC voltage
·		· 1.2 amps max = Amp Draw
		Kit includes a snap-on polycarbonate black bezel that will hide the screw heads for a clean installation
		25 customer selectable flash patterns, including steady on
Constitution of		Maximum light output in a minimum package
	CDLS306C-AW	No need to install a separate flasher unit; it's built into this miniature housing
		Lens has diffusing optics for wider coverage
		Circuitry is fully encapsulated within the housing for vibration and water resistance
		Interior/exterior mount
		· 10-30V DC voltage
		· 1.2 amps max = Amp Draw
	CDLS306-AA	Kit includes a snap-on polycarbonate black bezel that will hide the screw heads for a clean installation
		25 customer selectable flash patterns, including steady on
		Maximum light output in a minimum package
(Million)		No need to install a separate flasher unit; it's built into this miniature housing
		Lens has diffusing optics for wider coverage
		Circuitry is fully encapsulated within the housing for vibration and water resistance
		Interior/exterior mount
		• 10-30V DC voltage
		• 1.2 amps max = Amp Draw

Note: CDLS306-AW/CDLS306C-AW/CDLS306-AA are all the same. The difference is the color of the lights and the bezel. A =Amber W=White C=Chrome bezel

Thin AUX. LED W/ Rectangular Beezel:

Description	Part No.	Features
THIN AUX. LED W/ RECTANGULAR BEZEL Amber/Amber	CDLXT-121-AA	 Standard warning LED light 21 customer selectable flash patterns, including steady-on Only ½" thick Can be mounted just about anywhere, interior or exterior Rectangular black bezel Amber/Amber split colors Built with fully encapsulated circuitry Optional brackets are available (special order required) Voltage = 10-16V DC Amp Draw = 0.3 amps @ 12V DC
THIN AUX. LED W/ RECTANGULAR BEZEL Amber/Amber	CDLXT-121C-AA	 Standard warning LED light 21 customer selectable flash patterns, including steady-on Only ½" thick Can be mounted just about anywhere, interior or exterior Rectangular chrome bezel Amber/Amber split colors Built with fully encapsulated circuitry Optional brackets are available (special order required) Voltage = 10-16V DC Amp Draw = 0.3 amps @ 12V DC

Thin AUX. LED W/ Rectangular Beezel Cont:

Description	Part No.	Features
THIN AUX. LED W/ RECTANGULAR BEZEL Amber/White	CDLXT-121-AW	 Standard warning LED light 21 customer selectable flash patterns, including steady-on Only ½" thick Can be mounted just about anywhere, interior or exterior Rectangular Black bezel Amber/White split colors Built with fully encapsulated circuitry Optional brackets are available (special order required) Voltage = 10-16V DC Amp Draw = 0.3 amps @ 12V DC
THIN AUX. LED W/ RECTANGULAR BEZEL Amber/White	CDLXT-121C-AW	 Standard warning LED light 21 customer selectable flash patterns, including steady-on Only ½" thick Can be mounted just about anywhere, interior or exterior Rectangular Chrome bezel Amber/White split colors Built with fully encapsulated circuitry Optional brackets are available (special order required) Voltage = 10-16V DC Amp Draw = 0.3 amps @ 12V DC

Note: CDLXT-121-AA/CDLXT-121C-AA/CDLXT-121-AW/CDLXT-121C-AW are all the same. The difference is the color of the lights and the bezel. A=Amber W=White C=Chrome bezel

Amber LED:

Description	Part No.	Features
3 AMBER LED FLUSH MOUNT	CDLX3-A	 Voltage = 10-16V DC Amp Draw = 0.29 amps 25 customer selectable flash patterns, including steady-on. Versatile LED warning lights that are built with fully encapsulated circuitry Can be mounted just about anywhere, interior or exterior Snap-on Black bezel Optional mounting brackets are also available (need to place a special order)
4 AMBER/WHITE LED FLUSH MOUNT	CDLX4C-AW	 Snap-On chrome bezel Voltage = 10-30V DC Amp Draw = 0.7 amps @ 12V DC, 0.3 amps @ 24V DC Amber/White split colors 25 customer selectable flash patterns, including steady-on. Versatile LED warning lights that are built with fully encapsulated circuitry Can be mounted just about anywhere, interior or exterior Optional mounting brackets are also available (need to place a special order)
6 AMBER LED	CDLX6-AA	Amber/Amber split colors Voltage = 10-30V DC Amp Draw = 0.9 amps @ 12V DC, 0.5 amps @ 24V DC 25 customer selectable flash patterns, including steady-on. Versatile LED warning lights that are built with fully encapsulated circuitry Can be mounted just about anywhere, interior or exterior Optional mounting brackets are also available (special order required) Snap-on black bezel Designed for bracket mounting only Incorporates a heavy duty heat sink

More Lights:

Description	Part No.	Features
LED PAR36 WHITE HAZARD TURN	CLDHT362-T-C	 Clear lens Swivel mount Quick installation in any situation 32 customer selectable flash patterns, including steady-on Turn signal input Trapezoidal Voltage = 10-30V DC Amp Draw = 1.1 amps max
AMBER HALOGEN TEARDROP LIGHT	C1166HMA-24	 Aerodynamic light is ideal for unmarked cars or volunteers Voltage = 24V DC Cigarette plug with light on/off switch Magnet mount
AMBER PANCAKE LIGHT WITH MAGNET MOUNT	C1169HMA-24	 Low profile design, allows it to fit under sloping windshields with minimum obstruction and visibility Wide angle reflector for longer flash duration and brighter pulse Voltage = 24V DC Cigarette plug with light on/off switch Magnet mount
AMBER CONTOUR M-TECH PLUS MINIBAR	C9100LEDV-A	 Extremely low profile, made to "contour fit" to the roof of your vehicle Super bright LED technology Provides a superior warning light image Injection molded polycarbonate base is combined with two rubber coated vacuum magnets to "custom mount to your vehicle" 12" cigarette plug with lighted on/off and pattern select switch 20 customer selectable flash patterns 10-16V DC voltage 2.3 amps max = Amps draw
LAMP GROUP	1081029	 Revolving light Magnet mount Voltage = 24V DC Amp Draw = 4.0 amps (50 watt) Rugged die-cast aluminum base Enclosed bottom Patented shock mounted rotators with two sealed roller bearings provide quiet, smooth, and maintenance free operation Lock-and stay bulbs are field replaceable Durable polycarbonate plastic outer domes keep our lights corrosion, weather, and impact resistant
LAMP GROUP	2843757	 LED Amber lens Durable, lightweight polycarbonate, universal flange base: three-hole permanent mount 28 customer selectable flash patterns including steady-on Fully encapsulated circuitry for weather and shock resistance Interchangeable lens Voltage = 10-30V DC Amp Draw = 0.4 amps @ 12V DC, 0.8 amps max

^{*} Other part no. not included in the list are available. Please contact your sales representative if you have any questions. †All LED lights have a 5 year warranty Part Numbers are used for reference purposes only.